



An ISO 9001:2015 Company

HUMIDITY & TEMPERATURE METER

MODEL - KM 8010MK-1

FEATURES :

- * Data record
- * Data retrieving
- * Data deleting
- * Automatic power off
- * LCD backlight display
- * Max & Min Reading
- * Data Hold

ELECTRICAL SPECIFICATIONS :

Function	Range	Resolution	Max Response Time
Surrounding Temperature	-20°C~70°C(-4°F~158°F)	±1°C ⁽¹⁾	30s
RF Range	0% ~ 100%RH	±4%RH ⁽²⁾	30s
Dew Point Range	-20°C~50°C	±2°C ⁽³⁾	30s
Wet Bulb Range	-20°C~50°C	±2°C ⁽⁴⁾	30s

⁽¹⁾ Temperature Accuracy : ±1°C between 5°C ~ 50°C (41°F ~ 122°F).

⁽²⁾ Humidity Accuracy : ±4%RH (25°C(77°F) / 10%RH~90%RH), Full range accuracy is ±5%RH.

^{(3)/(4)} Dew point & wet bulb : ±2°C (5°C ~ 50°C(41°F ~ 122°F) / 10% RH ~ 90%RH).

- Battery : 1.5V x 3 AAA Battery
- Operating Current : Without Backlight : about 13mA
With Backlight : about 17mA
- Dimension : 184 x 56 x 36mm
- Weight : Approx. 129.2g.

ACCESSORIES :

Users Manual, Battery & Soft carrying pouch.



Preliminary Data

All specifications are subject to change without prior notice.



An ISO 9001:2015 Company

G-17, Bharat Industrial Estate, T. J. Road, Sewree (W), Mumbai - 400 015. INDIA.
 Sales Direct.: 022-24156638, 27754546 Tel. : 24124540, 24181649, 27750662, 27750292
 Email : sales@kusam-meco.co.in Web: www.kusamelectrical.com