

The meter can inspect particular objects or devices radiating low frequency electromagnetic waves. It can be used for power wire, computer monitor, TV, audio and visual, electromagnetic oven or analogous electrical installation.

SPECIAL FEATURES :

- * Reliable electromagnetic field measurement and quick response.
- * Simple operation.
- * Data hold function--hold the current data.
- * Peak Hold Function.
- * Peak hold function--only display new value when larger data value appear.

GENERAL SPECIFICATIONS :

- * **Measuring Range** : 0.1 ~ 400mG, 1 ~ 4000mG;
0.01 ~ 40mT, 0.1 ~ 400mT
- * **Accuracy** : \pm (4% rdg + 3 dgts) 50Hz / 60Hz
- * **Frequency** : 30Hz ~ 400Hz
- * **Exceed Measuring Range** : LCD will display "OL"
- * **Sampling Rate** : About 2 times per second
- * **Operating temperature** : 0°C~50°C; 0~70%RH.
- * **Storage temperature** : -10°C~60°C; 0~80%RH.
- * **Dimension** : 138 x 65 x 35 mm
- * **Weight** : 110gm
- * **Accessories** : Battery, Manual, & Carrying Case.



Preliminary Data

Note: All Specification are Subject to change without prior notice.