

KUSAM-MECO

An ISO 9001:2008 Company

HUMIDITY & TEMPERATURE METER

Model KM 920

GENERAL SPECIFICATIONS :

- Temperature Range : -10°C ~ 50°C (-30°C ~ 1000°C K-type)
- Temperature Accuracy : $\pm 1^\circ\text{C}$ or $\pm 1.8^\circ\text{F}$ ($\pm 3\%$ or $\pm 2^\circ\text{C}$ K-type)
- Temperature Resolution : 0.1°C / 0.1°F
- Humidity Range : 10% RH ~ 98% RH
- Humidity Accuracy : $\pm 3\%$ (in the 25°C; 30 ~ 95%RH);
 $\pm 5\%$ (in the 25°C; 10 ~ 30%RH)
- Humidity Resolution : 0.1% RH.
- °C / °F selection
- Display : Large LCD Temperature & Humidity dual Backlight display.
- Data Hold
- Sampling rate : 2.5 times / second
- Operating Temperature : 0°C ~ 50°C (32°F ~ 122°F) £80% RH non-condensing
- Storage Temperature : -10°C ~ 60°C (14°F ~ 140°F) 0% RH ~ 90% RH.
- Max / Min function
- K-type Thermocouple temperature measuring.
- CE approved.
- Low battery indication.
- Auto / Manual power off.
- Power Supply : Single 9V Battery.
- Dimension : 160 x 70 x 30 mm
- Weight : Approx. 308g (including battery)
- ACCESSORIES :
User Manual, K-Thermocouple, Probe, Carrying case & batteries.



Preliminary Data

All Specifications are subject to change without prior notice.

KUSAM-MECO

An ISO 9001:2008 Company

G-17, Bharat Industrial Estate, T. J. Road, Sewree (W), Mumbai - 400 015. INDIA.
Sales Direct.: 022-24156638, Tel. : 022-24124540, 24181649, Fax : 022-24149659
Email : kusam_meco@vsnl.net, Website : www.kusamelectrical.com