



This 50kΩ/V analog multimeter with its wide range of measurement capabilities, which includes a 10A AC range, is particularly designed for the requirement of electrical and electronic specialists and engineers. This instrument is also provided with meter over load protection and shock proof device.

### FEATURES

- High quality Taut Band movement.
- Easy to read 3-color scale : for mistake proof reading.
- Mirror scale : makes reading pointer easy.
- Safety features : on all ranges.
- Safety features : safety fused, safety "OFF" position.
- dB measurement.
- With stand : makes reading and measuring easy.
- EN 61010-1 CAT III 600V.  
EN 61326-1



AL-26

### SPECIFICATIONS

#### DC Voltage

Ranges	0.25/1/2.5/10/50/250/1000V
Accuracy	±2% F.S.
Sensitivity	50kΩ/V

#### AC Voltage

Ranges	2.5/10/50/250/1000V
Accuracy	±3% F.S.
Sensitivity	10kΩ/V
Decibelmeter	-20 to 62dB 0dB=1mW/600Ω Direct Scale : -20 to + 10dB

#### DC Current

Ranges	25µA-1mA-25mA/500mA, 10A(on separate input)
Accuracy	±2% F.S.
Sensitivity	250mV

#### AC Current

Ranges	10A
Accuracy	±3% F.S.

#### Resistance

Ranges	Rx10.2 to 20kΩ Rx102 to 200kΩ Rx10020 to 2MΩ Rx1K200 to 20MΩ
Accuracy	±3% of F.S. length

#### General

Power Source	1.5V(AA) x 2
Dimension	160(L)x100(W)x45(D)mm
Weight	380g(battery included)
Accessories	Test Leads Instruction manual Batteries

All Specifications are subject to change without prior notice.